



1971-74 Coronet, Super Bee, Charger, R/T 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (B Body)															
oe front		14		6.00		0.00		3.50		3.50					
oe rear		14		6.00		0.00		3.50		3.50					
	dia.	width	part # prefix	part # suffix	offset mm	bpace in	fspace in	stick out/ oe	32	82	92	95			
front	15	3.75	82	92	-537140	-25.40	1.38	3.38	-0.13		XX	XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front	15	5.00	92		-550144	-15.80	2.38	3.62	0.12			XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front	15	6.00	32		-560130	-12.00	3.03	3.97	0.47	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (82 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front/rear	15	7.00	92		-570146	-12.70	3.50	4.50	1.00		XX		601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front/rear	15	7.00	32		-570140	0.00	4.00	4.00	0.50	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front/rear	15	8.00	82	92	-580148	0.00	4.50	4.50	1.00		XX	XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front/rear	15	8.00	32		-580145	0.00	4.50	4.50	1.00	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
rear	15	10.00	92		-510150	0.00	5.50	5.50	2.00			XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 70.5hr)	
rear	15	10.00	32		-510150	-12.00	5.03	5.97	2.47	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front	17	4.50	82	92	-745142	-25.40	1.75	3.75	0.25		XX	XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front	17	6.00	32		-760135	0.00	3.50	3.50	0.00	XX			605-21416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.38 long SHANK, 70.5hr)	
front/rear	17	7.00	92		-770147	6.40	4.25	3.75	0.25			XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front/rear	17	7.00	95		-770147	6.40	4.25	3.75	0.25			XX	605-21416-10/20 (CLOSED)	1/2 closed lug kit, (95 series) (ACORN LUG NUT)	
front/rear	17	7.00	32		-770140	0.00	4.00	4.00	0.50	XX			605-41416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front/rear	17	8.00	32		-780145	0.00	4.50	4.50	1.00	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
rear	17	9.00	32		-790145	-12.00	4.53	5.47	1.97	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front	18	7.00	32		-870140	0.00	4.00	4.00	0.50	XX			605-11416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.68 long SHANK, 70.3hr)	
front	18	10.00	32		-810150	-12.00	5.03	5.97	2.47	XX			605-11416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.68 long SHANK, 70.3hr)	
front/rear	20	8.50	32		-085148	0.00	4.75	4.75	1.25	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
rear	20	10.00	32		-010150	-12.00	5.03	5.97	2.47	XX			605-11416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.68 long SHANK, 70.3hr)	
notes	c/c														
1973-80 Dart 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (B Body)															
oe front		14		6.00		0.00		3.50		3.50					
oe rear		14		6.00		0.00		3.50		3.50					
	dia.	width	part # prefix	part # suffix	offset mm	bpace in	fspace in	stick out/ oe	32	82	92	95			
front	15	3.75	82	92	-537140	-25.40	1.38	3.38	-0.13		XX	XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front	15	5.00	92		-550144	-15.80	2.38	3.62	0.12			XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front	15	6.00	32		-560130	-12.00	3.03	3.97	0.47	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front/rear	15	7.00	92		-570146	-12.70	3.50	4.50	1.00		XX	XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front/rear	15	7.00	32		-570140	0.00	4.00	4.00	0.50	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front/rear	15	8.00	82	92	-580148	0.00	4.50	4.50	1.00		XX	XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front/rear	15	8.00	32		-580145	0.00	4.50	4.50	1.00	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front	17	4.50	82	92	-745142	-25.40	1.75	3.75	0.25		XX	XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 lug kit, (82/92 series) (13/16 x 1.38 long SHANK, 63.91 hr)	
front	17	6.00	32		-760135	0.00	3.50	3.50	0.00	XX			605-21416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.38 long SHANK, 70.5hr)	
front/rear	17	7.00	92		-770147	6.40	4.25	3.75	0.25			XX	601-1416D-10 (closed), 601-1426D-10 (open)	1/2 closed lug kit, (95 series) (ACORN LUG NUT)	
front/rear	17	7.00	95		-770147	6.40	4.25	3.75	0.25			XX	605-21416-10/20 (CLOSED)	1/2 closed lug kit, (95 series) (ACORN LUG NUT)	
front/rear	17	7.00	32		-770140	0.00	4.00	4.00	0.50	XX		XX	605-41416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front/rear	17	8.00	32		-780145	0.00	4.50	4.50	1.00	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
rear	17	9.00	32		-790145	-12.00	4.53	5.47	1.97	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
front	18	7.00	32		-870140	0.00	4.00	4.00	0.50	XX			605-11416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.68 long SHANK, 70.3hr)	
front/rear	20	8.50	32		-085148	0.00	4.75	4.75	1.25	XX			605-31416-10/20 (CLOSED)	1/2 closed lug kit, (32 series) (13/16 x 1.00 long SHANK, 70.5hr)	
notes	c/c														
05-10 Chrysler 300C/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"															
05-08 Dodge Magnum/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"															
06-10 Dodge Charger/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"															
oe front		20		9.00		20.00		5.79		4.21					
oe rear		20		9.00		20.00		5.79		4.21					
	dia.	width	part # prefix	part # suffix	offset mm	adj offset	bpace in	fspace in	stick out/ oe	32	82	92	95		
front	17	4.50	92		-745442	-25.40	1.75	3.75	-0.46			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
front	17	4.50	95		-745442	-25.40	1.75	3.75	-0.46			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
front	17	7.00	92		-770447	6.40	4.25	3.75	-0.46			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
front	17	7.00	95		-770447	6.40	4.25	3.75	-0.46			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
rear	17	9.50	92		-795452	22.50	6.14	4.36	0.15		XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)	
rear	17	10.50	95		-705453	27.00	6.81	4.69	0.47		XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)	
front	18	5.00	92		-850445	-3.00	2.88	3.12	-1.09			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
front	18	5.00	95		-850445	-20.00	2.21	3.79	-0.43			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
front/rear	18	8.50	95		-885142	28.00	5.85	3.65	-0.56			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
front/rear	18	6.00	92		-060446	-8.90	3.15	3.85	-0.36			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
front/rear	20	9.00	92		090451	22.00	5.87	4.13	-0.08			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
notes	c/c														
WHEN USING A 17" REAR WHEEL, COMPRESSION OF THE REAR SUSPENSION OR A SHORTER SWAY BAR LINK IS REQUIRED															
17x11 TO BE USED WITH WIDE BODY APPLICATIONS															
6 PISTON HELLCAT FRONT BRAKE APPLICATIONS REQUIRE AN 18X5.00 OR 20X6.00 FRONT WHEEL, 20X9 ON FRONT REQUIRES HUBCENTRIC SPACER															
12-CURRENT Chrysler 300C/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"															
12-current Dodge Charger/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"															
09-current Dodge Challenger/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"															
oe front		20		9.00		20.00		5.79		4.21					
oe rear		20		9.00		20.00		5.79		4.21					
	dia.	width	part # prefix	part # suffix	offset mm	adj offset	bpace in	fspace in	stick out/ oe	32	82	92	95		
front	17	4.50	92		-745442	-25.40	1.75	3.75	-0.46			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
front	17	4.50	95		-745442	-25.40	1.75	3.75	-0.46			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
front	17	7.00	92		-770447	6.40	4.25	3.75	-0.46			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
front	17	7.00	95		-770447	6.40	4.25	3.75	-0.46			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
rear	17	9.50	92		-795452	22.50	6.14	4.36	0.15		XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)	
rear	17	10.50	95		-705453	27.00	6.81	4.69	0.47		XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)	
front	18	5.00	92		-850445	-20.00	2.21	3.79	-0.43			XX	XX	601-1432-10/20 (closed), 601-1434-10/20 (open)	14mm lug kit, (92 series) (7/8 x 1.38 long SHANK, 71.50 hr)
front	18	5.00	95		-850445	-20.00	2.21	3.79	-0.43			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
front/rear	18	8.50	95		-885142	28.00	5.85	3.65	-0.56			XX	XX	602-2428-10/20 (closed)	14mm lug kit, (95 series) (3/4 conical seat/ acorn)
front/rear	20	9.00	92		090451	22.00	5.87	4.13	-0.0						

WHEN USING A 17" REAR WHEEL, COMPRESSION OF THE REAR SUSPENSION OR A SHORTER SWAY BAR LINK IS REQUIRED													
17x11 TO BE USED WITH WIDE BODY APPLICATIONS													
6 PISTON/ HELLCAT FRONT BRAKE APPLICATIONS REQUIRE AN 18X5.00 OR 20X6.00 FRONT WHEEL, 20X9 REQUIRES HUBCENTRIC SPACER													
<b>15-CURRENT Chrysler/Dodge AWD 5x115, 71.5mm id, 14mm x 1.5, 35-45mm OE OD 29.2"</b>													
oe front	19	7.50			55.00		6.42	2.08					
oe rear	19	7.50			55.00		6.42	2.08					
	<i>dia.</i>	<i>width</i>	<i>part # prefix</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>	<b>32</b>	<b>82</b>	<b>92</b>	<b>95</b>
front	17	4.50	92	-745442	-25.40	-6.00	2.51	2.99	0.90			XX	
front	17	7.00	92	-770447	6.40	25.00	4.98	3.02	0.93			XX	
rear	17	9.50	92	-795153	43.50	62.00	7.69	2.81	0.72			XX	
front/ rear	18	8.50	92	-885152	28.00	47.00	6.60	2.90	0.81				XX
rear	20	6.00	92	-060446	-8.90		3.15	3.85	1.77			XX	
front/ rear	20	9.00	92	090451	22.00		5.87	4.13	2.05			XX	
<i>notes</i> /c/													
WHEN USING A 17" REAR WHEEL, COMPRESSION OF THE REAR SUSPENSION OR A SHORTER SWAY BAR LINK IS REQUIRED													
17x11 TO BE USED WITH WIDE BODY APPLICATIONS													
6 PISTON/ HELLCAT FRONT BRAKE APPLICATIONS REQUIRE AN 18X5.00 OR 20X6.00 FRONT WHEEL, 20X9 REQUIRES HUBCENTRIC SPACER													